

# TECHNICAL SPECIFICATIONS

TEST SPECIFICATION	STANDARD	RESULTS
Application Type	ISO 10874	33, Heavy Commercial
Static Load Limit	ASTM F970	2,000 PSI
Squareness & Straightness	ISO 24342 ASTM F2055	Passes No Deviation, ≤0.1mm
Flexibility	ASTM F137	Passes
Dimensional Stability	ASTM F2199	Passes
Resistance to Chemicals	ASTM F925	Passes, No defects
Resistance to Light	ASTM F1515	Passes
Resistance to Heat	ASTM F1514	Passes
Fire Resistance	ASTM E648	Passes
Smoke Density	ASTM E662	Passes
Slip Resistance	ASTM E303	Passes
Indoor Air Quality		Low VOC, Floor Score Certified
Dynamic Coefficient of Friction	ANSI A326.3	0.43

# PACKAGING SPECIFICATIONS


SIZE	THICKNESS	SF/CARTON	LB/CARTON	CARTON/PLT SF/PLT
23.62" x 23.62"	3mm	38.75 sf	36.43 lb	40 ctns 1,550 sf



NO WAX



ANTIBACTERIAL



DIMENSIONAL  
STABILITY



SCRATCH  
RESISTANCE



STAIN  
RESISTANCE



EASY  
MAINTENANCE